

LINER SEVEN 50 KAO

Concrete Demolder Admixture (Surface Aesthetics Enhancement Type)

LINER SEVEN 50 is an aqueous demoulder for application in steel molds. By inhibiting concrete to mold adhesion, LINER SEVEN 50 minimizes surface bubbles; allowing for aesthetically pleasing concrete with no uneven surface coloration.

Features

- Minimal surface bubbles, non-oily aesthetic finish
- Reduced concrete staining as compared to standard demolders
- Steel demolder rust inhibition effects
- High flash point – superior fire safety
- Non-freezing even at low temperature conditions
- Stable aqueous emulsion



Usage Method

- Standard usage / 1:4 water:LINER SEVEN 50 dilution
- Apply with either brushes, rollers, cloth, mops, or sprays.
- Apply 1L of dilution to a coating area of 30m².

Properties

Appearance	: Translucent light brown liquid
Density(20°C g/cm ³)	: 0.890~0.920
Viscosity(20°C mPa·s)	: 100~200
Emulsifying rate(mL)	: ≥ 55
Flash point	: ≥200°C
Freezing point	: ≤-5°C

Packaging

16kg can, 180kg drum

The information and recommendations in this publication are to the best of our knowledge reliable. However, nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purpose. For more enquiries, please contact the following.

Kao Corporation Chemical Business Eco Infrastructure

Sumida Office 2-1-3 Bunka, Sumida-ku, Tokyo 131-8501

Osaka Office 1-4-1 Itachibori, Nishi-ku, Osaka, Osaka Prefecture 550-0012

HP : <https://chemical.kao.com/jp/>

Mail : chemical_eif@kao.com